

Quick™ QLX & QLXN Series

Economical, thermoplastic LED exit signs



Construction

- UV stabilized thermoplastic body
- 6 inch EXIT lettering legend, available in red or green
- Field selectable chevrons

Mounting

- Surface mount
- Canopy included for end or ceiling mount applications
- Universal J-Box mounting

Finishes

Mist white

Electronics

- Optional Improved Diagnostics
- 120/277 60Hz
- Sealed maintenance free Nickel-Cadmium battery for self-powered models

Approvals

- UL 924 listed
- Damp location 50°F to 104°F (10°C to 40°C)
- UL 94, 5VA flame rated


Warranty (subject to proper installation and maintenance)

Three-year full warranty

Detailed warranty terms located on **page 182** or online at: www.lightalarms.com



Dimensions (Dimensions are approximate and subject to change):



Power consumption chart

AC input

120/277VAC, 60Hz maximum 2.5W

Accessories (Order as a separate item)

Description	Product code
Wire guard (wall mount)	WG1-L
Wire guard (ceiling mount and end mount)	WG5-L

Ordering format

Series	Legend color	Options
QLX500= AC-Only	RN= Red	Blank= No option
QLXN500= Self-powered	GN= Green	-ID= Improved Diagnostics (audible) ¹
		-RID= Remote capacity 3.6V-3.6W Improved Diagnostics (audible) ^{1, 2}

Example: QLXN500RN

¹ Available with red legend only

² Remote capacity for (1) ELF612D/LED or (2) ELF612/LED remote heads only