

Weatherproof or Harsh Environment Remote Series

ELF647, ELF647D

DESCRIPTION: NEMA CLASSIFIED.
Single, PAR36 size lighting head with fully adjustable swivel, all thermoplastic construction, and stainless steel screws. Standard with round aluminum plate for mounting directly to 4" outlet box. Fixtures are rain and dust-tight as well as corrosion resistant.

FINISH: Mist White (-M), Gray (-G), Black (-B)

MOUNTING: Standard with round plate for mounting directly to 4" outlet box.

LAMPS: Wedge base incandescent • Bi-pin halogen • PAR36 sealed beam

VOLTS: 6 or 12Vdc.

MAXIMUM WATTS:

25 watts per head



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF647	/ ____ - ____	____	____

ELF647C

DESCRIPTION: Class I Division 2, Group A, B, C and D
Single lighting head with fully adjustable swivel - with gasketed aluminum canopy and junction box

FINISH: Black (-B)

MOUNTING: Standard with round plate for mounting directly to 4" outlet box

LAMPS: Wedge base incandescent
• Bi-PIN Halogen • PAR36 sealed Beam

VOLTS: 6 or 12 volt

MAXIMUM WATTS: 12 watts per head



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF647C	/ ____ - ____	____	____

ELF647, ELF647D

DESCRIPTION: NEMA CLASSIFIED.
Single, PAR36 size lighting head with fully adjustable swivel, all thermoplastic construction, and stainless steel screws. Standard with round aluminum plate for mounting directly to 4" outlet box. Fixtures are rain and dust-tight as well as corrosion resistant.

FINISH: Mist White (-M), Gray (-G), Black (-B)

MOUNTING: Standard with round plate for mounting directly to 4" outlet box.

LAMPS: Wedge base incandescent • Bi-pin halogen • PAR36 sealed beam

VOLTS: 6 or 12Vdc.

MAXIMUM WATTS:

25 watts per head



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF647	/ ____ - ____	____	____

ELF647DC

Description: Class I Division 2, Group A, B, C and D
Double lighting head with fully adjustable swivel - with gasketed aluminum canopy and junction box

FINISH: Black (-B)

MOUNTING: Standard with round plate for mounting directly to 4" outlet box

LAMPS: • Wedge base incandescent
• Bi-pin halogen
• PAR36 sealed Beam (6 or 12Vdc)

VOLTS: 6 or 12 volt

MAXIMUM WATTS: 12 watts per head

Wattage doubles for "D" 2-lamp version



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF647DC	/ ____ - ____	____	____

ELF650

DESCRIPTION: Nema-4X Rated,
single head complete with gasketed cast aluminum backplate and clear UV impact resistant case.

FINISH: Mist White (-M), Black (-B), Gray (-G)

MOUNTING: Direct to 4" octagonal electric box

LAMPS: MR16 Halogen • LED lamps

VOLT: 6, 12 or 24 volt

MAXIMUM WATTS: 20 watts per head



NEMA-4X



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF650	/ ____ - ____	____	____

PATENT PENDING

ELF650D

DESCRIPTION: Nema-4X Rated,
double head complete with gasketed cast aluminum backplate and clear UV impact resistant case.

FINISH: Mist White (-M) (standard),
Black (-B), Gray (-G)

MOUNTING: Direct to 4" octagonal electrical box

LAMPS: MR16 Halogen • LED

VOLTS: 6, 12 or 24 volt

MAXIMUM WATTS:
20 watts per head

Wattage doubles for "D" 2-lamp version



NEMA-4X



Remote Fixture Model #	Lamp Suffix	Color	Voltage
ELF650D	/ ____ - ____	____	____

PATENT PENDING